

Wiegand Data Interface

The data containing the CSN is transmitted via a data pair (D1, D0).

Audio/Visual Indication

A Green LED and Beeper can be controlled by ALK370x-IP lock controllers for audio and visual indication.

Secure

All RF data transmission between the card and reader is encrypted using a secure algorithm.

Optimal Read Range

An auto-tuning feature automatically adjusts the reader for optimal read range performance on any mounting surface.



WGR3606-WR

WGR3606-WR contactless readers make access control more powerful, more versatile and offer enhanced security through data encryption and mutual authentication between the card and reader.

WGR3606-WR DESFIRE card readers are designed for optimal performance with the Netgenium ALK370x-IP family of lock controllers.

The readers source their power from the ALK370x-IP controllers, which in turn are powered from an IEEE802.3af POE device.

Technical Data

Model Number:

WGR3606-WR

Read Range:

Mifare Card (CSN) : Up to 2.0" (5.1 cm)

Mounting:

A two-part reader makes installation easier. The mounting plate attaches to any flat surface and the reader body fits onto the mounting plate. The cover fits over the reader body and is secured with a screw.

An auto-tuning circuit provides consistent read ranges on various mounting surfaces with minimal reduction on metal surfaces.

Dimensions:

1.9" x 4.0" x 0.9"

4.8 cm x 10.3 cm x 2.3 cm

Power Supply:

12 VDC from ALK370x-IP

Current:

55mA AVG, 116mA PEAK

Operating Temp:

-31° to 150° F (-35° to 65° C)

5% to 95% relative humidity non-condensing